

PORTABLE
BELT CONVEYOR

TRANSFER HOPPER



MOVES A WORLD OF GRAIN
Hutchinson
THE WORLD OVER

Convenient, Gentle, and Amazingly Efficient.

The Model 1015 Portable Belt Conveyor Transfer Hopper features a full 10" diameter capacity. The main tube is constructed of heavy 14 gauge galvanized tubing. The 2-ply conveyor belt features a full 15" width. Other basic dimensions include:

Hopper Clearance – 7-1/2" (Canvas Collapsed)

Discharge Height - 30"

Hopper Intake Size - 35" x 65"




LOW PROFILE TRANSFER HOPPER

The low profile hopper requires only 7-1/2" of clearance. A spring loaded


canvas extension expands capacity and productivity. The low profile hopper design provides superior performance in limited space situations commonly encountered with gravity wagons, hopper bottom semi-trucks or horizontal bin unloaders.



DRIVE OPTIONS



The Portable Belt Conveyor Transfer Hopper can be powered by your choice of a 5 hp Electric Motor (not included) or a Hydraulic Motor.



SWING AWAY KIT

The optional Swing-Away Kit includes hopper pivot wheels and a discharge spout swivel bracket. This kit allows the portable unit to be adapted to an existing Hutchinson or Mayrath Portable Belt Conveyor for added versatility on your operation.



INTEGRATED INCLINE ADJUSTMENT



A jack stand integrated into the side of the unit lets you quickly adjust the incline of the discharge.

TOWING KIT



The optional Towing Kit includes the basic undercarriage with roadway wheels, tires and hitch. The kit can be quickly adapted and ready for transport.

CALL TOLL-FREE 1-800-523-6993
For more information.

Distributed by:



HUTCHINSON

A Division of GLOBAL Industries, Inc.
P.O. Box 629 • Clay Center, Kansas 67432
Ph. (785) 632-2161 • FAX (785) 632-5964
www.hutchweb.com