

SQUEEZE BELT[®]

*U.S. Patent: 6,484,870

CONVEYOR



MOVES A WORLD OF GRAIN
Hutchinson
THE WORLD OVER

Complimented by Comparison.

Higher Volume. Steeper Inclines. Less Damage.



High & Low Speed Range Selection:
Versatile Jackshaft or Direct Pulley Drive



The Squeeze Belt® Conveyor features an Intake Transfer Hopper with independent adjustable hopper side panels. The hopper features a length of 70" with a width of 42" and a minimum hopper height of 10".



Wind guards are standard for belt protection and safety. Rollers are strategically located to reduce friction and wear on the belts.



The Intake Transfer Hopper folds back over the main drive assembly during transport.



The gentle squeeze of the bottom and top belts convey more volume up steeper inclines with less product damage.



Exclusive Belt Alignment Guide Rollers maintain proper belt tracking for optimum belt life.

LENGTH AND DISCHARGE HEIGHT

LENGTH	DISCHARGE HEIGHT	HP ELEC.	HP PTO
35'	19'-1½"	25	50
45'	24'-10"	30	60
60'	36'-5"	40	65
70'	42'-3½"	50	70
90'	54'-7"	60	100

(Capacity Ratings for dry corn at 35 degrees with Hitch Conveyor attached)

BENEFITS of the Squeeze Belt® Conveyor

CAPACITY: Capacities will range from 4,000 to 9,000 BPH, based on the drive selection and desired belt speed.

CONSTANT CAPACITY: Based on dry corn at 35 degree inclines the Squeeze Belt® Conveyor out performs all other single belt conveyors by preventing product roll back.

GENTLE HANDLING: The Squeeze Belt® technology maintains grain quality and protects seed germination by gently squeezing a volume of product between two moving belts.

LONG LIFE CHARACTERISTICS: Belts, transition pans and our unique belt roller guide system were designed for long lasting performance with 2 heavy duty two-ply 15" Crescent Top PVC belts with nylon slider backs. Belt life is rated at 3,000 hours of operation.

ENERGY EFFICIENT: The Squeeze Belt® Conveyor offers long-term energy savings for the amount of horsepower required verses the amount of grain moved.

DESIGN: All units feature a durable powder coat finish. The main housing is a rugged 10" galvanized tube for maximum durability.

DRIVE OPTIONS: Both PTO Drive and Electric Drive options are available.

INTAKE TRANSFER HOPPER DRIVE OPTIONS: Tail Roller, V-Belt Drive or Hydraulic Drive.

SQUEEZE BELT® CONVEYOR ACCESSORIES: Seed Hopper Attachment, Dolly Wheel, and Flex Tubing.

*U.S. Patent: 6,484,870



A Division of GLOBAL Industries, Inc.
P.O. Box 629 • Clay Center, KS 67432
Ph. (785) 632-2161 • FAX (785) 632-5964
www.hutchweb.com

Call Toll-Free
1-800-523-6993
For more information.

Distributed by: