

# TRAC MASS-TER

PORTABLE VERSATILITY



- Operate from the comfort of a tractor cab.
- Attachment to the tractor is as quick as aligning and installing three pins followed by hydraulic and PTO connections. With attachments at the front and rear of the tractor, the conveyor moves with the tractor just as a mounted unit.
- **Self Supporting Undercarriage**  
Totally self-supporting even when not attached to the tractor.

***10,000 BPH Tractor Mounted Conveyor***

***Complimented by Comparison.***

# TRAC MASS-TER



The Hutchinson Trac Mass-ter is a unique conveyor. Two industry-preferred conveying methods are combined to maximize efficiency and minimize wear. A large diameter, low speed screw in the hopper moves grain to the inclined chain conveyor where UHMW paddles quickly but gently carry the material from intake to discharge. Patterned after the model 85 Mass-ter Mover, the Trac Mass-ter incline conveyor is a versatile performer that has been utilized in horizontal or inclined applications on many large farms and commercial operations. It performs well where low horsepower requirements, quiet operation, gentle handling and longevity are important. Combined with the large 16" screw conveyor intake, this product is ready for those jobs requiring day after day operation.

## HYDRAULIC LIFT UNDERCARRIAGE

Raising and lowering is done easily and smoothly with your tractor's hydraulics.



## OPTIONAL HYDRAULIC ADJUSTABLE SPOUT

Use the optional hydraulic swivel spout to vary the discharge point to facilitate truck load out.



## ACCESSORIES

- Hydraulic Adjustable Spout
- Hydraulic Swivel Spout
- Enclosed Intake Hopper Assembly
- Adaptor kit for Cat. #3 three-point hitch.

## OPTIONAL INTAKE HOPPER ASSEMBLY

Use the Optional Intake Hopper to fill your flat storage facilities.



## TRAC MASS-TER SPECIFICATIONS

Capacity	10,000 BPH
Length	40'
Discharge Height	Adjustable-12' 6" to 21' 6"
Discharge Lift	Hydraulic Cylinder
Undercarriage Lift	Tubular, Welded
Wheels	Two, caster, less tires
Inclined Conveyor	7"x13" En masse
Conveying Medium	Heavy Duty Chain and Ultra High Molecular Weight (UHMW) Paddles
Gathering Conveyor	16" Screw Conveyor, 10' 0" wide
Drive	Minimum 60 HP, 540 RPM
Tractor Size	90 HP or larger for handling efficiency 8' 6" maximum tractor width
Conveyor Drive	Bottom, Double #80 Roller Chain
Tractor Attachments	Rear Two Points Cat. #2 Single Front Attachment
Conveyor Speed	Chain 397 feet per minute Screw 114 RPM

Call Toll-Free

# 1-800-523-6993

For more information.

Distributed by:



A Division of **GLOBAL** Industries, Inc.  
P.O. Box 629 • Clay Center, KS 67432  
Ph. (785) 632-2161 • FAX (785) 632-5964  
[www.hutchinson-mayrath.com](http://www.hutchinson-mayrath.com)